



EP 00 Technical Data

FEATURES

- A TRUE PREMIUM QUALITY MULTIPURPOSE GREASE
- CAN BE USED OVER A WIDE TEMPERATURE RANGE
- ULTRA MODERN CALCIUM COMPLEX THICKENER
- SHEAR STABLE OVER THOUSANDS OF CYCLES
- HIGH DROPPING POINT – A GOOD HIGH TEMPERATURE GREASE
- HIGH EP
- NO MOLY DISULFIDE
- OUTSTANDING WATER RESISTANCE
- OUTSTANDING CORROSION PROTECTION

TYPICAL TEST DATA

TEST	ASTM METHOD	TYPICAL RESULT
NLGI Grade	00	
Base Oil		
Viscosity @ 100°C., cSt	D 445	12.5
Viscosity @ 40°C., cSt	D 445	220
Viscosity Index	D 2270	95
Color	Purple	
Penetration @ 77°F		
Worked	D 217	420
Dropping Point °C, (°F)	D 2265	250 (482)
Four Ball Weld Point, Kgf	D 2596	620
Timken OK Load, Lbs.	D 2509	60
Wheel Bearing Life Test, Hrs.	D 3527	100
Wheel Bearing Leakage, 20 hs. 160 C, 1000rp	D 4290	NA
Water Washout	D 1264	6
Rust Protection	D 6138	0,0
Corrosion Protection	D 1743	PASS